Multi zone inverter mini split

TM18HFDI

General Features

- 2 Thermistor control
- 24-Hour on/off Timer
- Auto operation
- Auto restart
- Chaos swing
- Control lock function
- Drain Pump
- Inverter
- High And Low Pressure Protection Features
- Over Load Protection Features
- Over-Current Protection
- Anti Freeze Protection
- Wired controller
- Optional Wireless Remote control

Unit Performance:

Nominal Cooling Capacity (Btu/h)	15,300
Nominal Heating Capacity (Btu/h)	18,700

****

Set Temperature

Cooling (°F WB)	61～86
Heating (°F DB)	61～86

Piping

Liquid Line (in, OD)	1/4
Gas Line (in, OD)	1/2
Drain OD, ID (in)	1.57

Electrical Specification

Power Supply	208-230V / 60Hz
Communications Wire Size	AWG 14/4
Rated Amps (A)	0.43

Fan

Type	Centrifugal
Quantity	3
Motor/Drive	Direct Drive
Air Flow Rate (CFM)	412/353/294

Unit Specification

Refrigerant Type	R410A
Refrigerant Control	EEV
Sound Pressure (dB(A))	41/37/33
Primary Filter	Yes
Net Weight (lbs)	59.5
Dehumidification (Pt/h)	3.8

R410A

INVERTER

AHRI CERTIFIED www.ahridirectory.org

Job Name:		Date:	
System Reference No.:			
Engineer Signature:			

Specifications subject to change without prior notice.

© Gree Electric Appliances, Inc.of ZhuHai



Outline Dimension Diagram



	mm	Inch
A	942	37 3/32
B	491	19 21/64
C	862	33 15/16
D	820	32 9/32
E	900	35 7/16
F	615	24 7/32
G	982	38 21/32
H	156	6 9/64
I	200	4 7/8
J	635	25