

VRF Indoor

Indoor VRF SYSTEM FEATURES

- * Strong And Balanced Airflow
- * Ultra-Low Noise Operation
- * Intelligent Drainage
- * DC inverter Motor
- * Protection Function




TVRF-IE4WC07KHP

Specifications		Model Name
Unit Type		TVRF-IE4WC07KHP
Cooling Capacity	Btu/h	7,500
Heating Capacity	Btu/h	8,500
External Dimensions (WxHxD)	In.	33-1/8 x 33-1/8 x 7-1/2
	mm	840 x 840 x 190
Net Weight	Lbs. / Kg	50/22.5
Electrical Power Requirements	Voltage, Phase, Hertz	208/230V, 1-phase, 60HZ
Power Cooling Consumption	kW	0.048
Power Heating Consumption	kW	0.048
Current Cooling	A	0.3
Current Heating	A	0.3
Minimum Circuit Ampacity (MCA)	A	1
Max. Overcurrent Protection (MOCP) Fuse	A	15
Refrigerant Piping Dimensions (In./mm)	Liquid (High Pressure)	1/4 - 6.35
	Gas (Low Pressure)	3/8 - 9.52
Sound Pressure Level	dB(A)	36/34/31
<u>Fan</u>		
Type x Quantity		Centrifugalx1
Airflow Rate	CFM	440/385/325
<u>Motor</u>		
Motor Type x Quantity		BLDCx1
Motor Output	kW	0.035
Refrigerant		R410A
Coil Type		Fenestrate plain film --hydrophilic film
Unit Color		Silver

Job Name:		Date:	
System Reference No.:			
Engineer Signature:			

Outline Dimension Diagram



	A	B	C	D	E
mm	950	890	840	680	780
inch	37 3/8	35	33 1/8	26 3/4	30 3/4

